

S. No.	Properties		UOM	PRODUCT QUALITY : KITCHEN TOWEL (MAXI ROLL)			
				1 Ply	2 Ply	1 Ply	1 Ply
1	No. of Ply			1 Ply	2 Ply	1 Ply	1 Ply
2	Substance (1 Ply)		g/m ²	17 ± 0.5	17 ± 0.5	18 ± 0.5	19 ± 0.5
3	Thickness (1 Ply)		micron	106 ± 5	106 ± 5	111 ± 5	114 ± 5
4	Bulk		cdgm	6.2 ± 0.2	6.2 ± 0.2	6.2 ± 0.2	6.0 ± 0.2
5	Dry Tensile Strength	MD	gf/25mm	480 ± 50	950 ± 50	510 ± 50	510 ± 50
		CD	gf25mm	300 ± 25	595 ± 25	320 ± 25	320 ± 25
6	MDT/CDT RATIO			1.6 ± 0.2	1.6 ± 0.2	1.6 ± 0.2	1.6 ± 0.2
7	Stretch	MD	96	21 ± 1	21 ± 1	21 ± 1	21 ± 1
8	Wet Tensile Strength	MD	gf/50mm	120 ± 12	240 ± 25	125 ± 12	130 ± 12
9	Wet/Dry Tensile		96	24 ± 2	24 ± 2	24 ± 2	25 ± 2
10	ISO Brightness (Frank, PTI)		96150	87 ± 2	87 ± 2	87 ± 2	87 ± 2
11	Shade		-	Natural			
12	Furnish		-	Virgin pulp			
13	Core (ID)		mm	76			
14	Number of joints		-	7096 ZERO JOINT, 20% ONE JOINT 1096 TWO JOINTS			
15	Reel Diameter		mm	1200 Max.			
An ISO 9001 : 2008, ISO 14001:2004 & OHSAS 18001:2007 Company							